

【CLAIMS】

【Claim 1】

A drum type washing machine comprising:

- 5 a cabinet forming an exterior of the drum type washing machine;
- a tub provided within the cabinet;
- a damper having one end connected to the tub and the other end rotatably connected to the cabinet;
- a damper pin having predetermined elasticity and rotatably joining the damper to the
- 10 cabinet; and,
- an elastic member provided within the damper pin.

【Claim 2】

- The drum type washing machine of claim 1, wherein the elastic member comprises a
- 15 rubber having a predetermined elasticity.

【Claim 3】

- The drum type washing machine of claim 1, wherein the elastic member comprises a
- spring having a predetermined elasticity.

20

【Claim 4】

- The drum type washing machine of claim 1, wherein a slot is formed along a lateral
- side of the damper pin.

【Claim 5】

- The drum type washing machine of claim 1, wherein a hanging sill is provided to one

side of the damper pin and a hanging piece is provided to the other side of the damper pin to prevent the damper pin from being separated.

【Claim 6】

5 The drum type washing machine of claim 5, wherein the hanging piece is formed as one body with the damper pin.

【Claim 7】

10 The drum type washing machine of claim 6, wherein the hanging piece has a predetermined elasticity.

【Claim 8】

A drum type washing machine comprising:

a cabinet forming an exterior of the drum type washing machine;

15 a tub provided within the cabinet;

a damper having one end connected to the tub and the other end rotatably connected to the cabinet;

a damper pin rotatably joining the damper to the cabinet to have a slot along a lateral side of the damper pin; and

20 a felter provided within the damper pin.

【Claim 9】

The drum type washing machine of claim 8, wherein the felter is impregnated with a lubricant.

25

【Claim 10】

The drum type washing machine of claim 9, wherein the lubricant is an oil.

【Claim 11】

The drum type washing machine of claim 9, wherein the lubricant is a grease.

5

【Claim 12】

The drum type washing machine of claim 8, wherein the slot is formed along a lateral side of the damper pin.

10 **【Claim 13】**

The drum type washing machine of claim 8, wherein a hanging sill is provided to one side of the damper pin and a hanging piece is provided to the other side of the damper pin to prevent the damper pin from being separated.

15 **【Claim 14】**

The drum type washing machine of claim 13, wherein the hanging piece is formed as one body with the damper pin.

【Claim 15】

20 The drum type washing machine of claim 13, wherein the hanging piece has a predetermined elasticity.